

1

2

3

4

5

6

A

B

C

D

E

F

G

H

I

J

A

B

C

D

E


F

G


H

I

J



FOR USE WITH  
STMicroelectronics  
VIPer 50  
SECONDARY REGULATION



ELECTRICAL SPECIFICATIONS

L @ 1kHz .1V - (3-4) 900µH ±10%

LL @ 100kHz .1V - (3-4) 19µH TYP, TOL TBD  
(WITH 1,2,5-8 SHORTED)

URNS RATIO - ±3%  
3-4:1-2 - 1:0.125  
3-4:5-6 - 1:0.057  
3-4:7-8 - 1:0.19

DCR - OHMS TYP, TOL TBD  
3-4 - 1.73  
1-2 - 0.19  
5-6 - 0.008  
7-8 - 0.015

HIPOT - 5500VAC 1SEC  
N1,N2 TO N3,N4

NOTE:  
POLARITY SHOWN IS THE TRANSFORMER.  
FOR CORRECT FLYBACK OPERATION  
CONNECT B+ TO PIN 3.

NOTE:  
MEETS CONSTRUCTION FOR:  
UL 1310, 1950, 1411  
IEC 61558-1, 2-17, EN60950

REVISION		DATE	MARKINGS	LOCATION	
0	PRELIMINARY	01/10/00	CRAMER EIA DATE CODE CVP 30-012	PIN RAIL SIDE OF CORE	
1	CHANGED PIN OUTS	02/22/00	DESCRIPTION 15 VA FLYBACK,5,18	TOLERANCE UNLESS OTHERWISE SPECIFIED 2 PLACE DECIMALS ±.010 3 PLACE DECIMALS ±.005 FRACTIONS ±1/64 ANGLES ±1/2°	PROPRIETARY INFORMATION PROPERTY OF CRAMER COIL & TRANSFORMER CO. DUPLICATION AND/OR DISTRIBUTION BY PERMISSION ONLY
			CUSTOMER		
			G:\DATA\SPECS\ENG\CVP\30-012	CUSTOMER PART NUMBER	REV
			DR. CAM	DATE 01/10/00	CRAMER PART NUMBER CVP 30-012
			APPD. JDB	DATE 01/11/00	

1

2

3

4

5

6